



Marsh ENsign Range

Sewage Treatment Plants From 6 – 50PE
Uni:6 – 50



The ENsign Range of Sewage Treatments Plants is Certified to EN12566-3 and Designed in Accordance with British Water Loads & Flows Code of Practice

- Gravity & Pumped Outlet
- Shallow Invert 500mm
- Invert Risers Available
- Very Quiet Running
- Low Running Cost
- Stainless Steel Fixings
- Separate De-sludge Chamber
- Ex-stock normally within 72 hours

- ENsign Sewage Treatment Plants are extremely strong engineered to a minimum wall thickness of 5mm both internally and externally
- Powered by Energy Efficient Compressors
- Pumped Outlets are Jung U Range
- Compressor Alarms Are Standard
- Full Technical Design Service Available

BOD
15mg/litre



Marsh ENsign Range

www.marshindustries.co.uk

www.ensignsewagetreatment.co.uk

T. 0044 1933 653570

E. sales@marshindustries.co.uk



Uni 6-50PE Sewage Treatment Plants

Tested & Certified To EN12566-3 Tested in Aachen, Germany



Uni:ENsign 6-50PE Range

Hydraulic daily load:	1.2m ³ /day-10m ³ /day	
Material:	GRP	
Watertightness (water test):		Pass
Crushing resistance:		Pass
Treatment efficiency:	BOD:	Pass
	TSS:	Pass
	NH4:	Pass

Tested to BSEN12566-3: Aachen Germany

BOD 15mg/litre

Warranty & Guarantee

- The minimum design life of the tank structure is twenty five years. (internally & externally)
- The compressor blower is covered by a two year guarantee.
- The diffuser is covered by a five year guarantee.
- Wall thickness of the chamber internal and external is 5mm.
- All metal components stainless steel.



BRITISH WATER

sales@marshindustries.co.uk
www.marshindustries.co.uk
T.0044 1933 653570
F.0044 1933 651604

