



# Trojan:4 Sewage Treatment

Small Above or Below Ground Sewage Treatment  
Designed for Either Commercial Offices, Small  
Workshops or Domestic Application



Based upon the popular Marsh Uni:SaF Above ground plants, the Trojan 4 is designed to treat sewage for up to four people in domestic applications, or for small workshops, commercial premises or offices. The plant has been designed to the latest loads and flows criteria of the Environment Agency and the British Water Guidelines.

The Trojan:4 can be used for secondary treatment for failing septic tanks or sewage plants.

## The Maximum Daily Loading is:

Hydraulic Flow: 720 litres/day

BOD: 240mg/day

NH4 : 32mg/day

Retention time 50 hours. Ph neutral

- The Trojan:4 operates a continuous sludge return system for improved final effluent quality
- Standard inlet invert is 500mm
- But the plant can be manufactured for either shallower or deeper inlets.
- Gravity or pumped outlet.
- Extremely Strong Wall thickness 10mm
- Stainless Steel Fixings
- Media bed surface area 310m<sup>2</sup> per m<sup>3</sup>
- Bibus Secoh Compressors
- Variable Inverts , Easy Desludge
- Silent Running and Low Maintenance
- Compressor Alarm Included
- RCD Box Included
- All Internal Components Easily Accesible
- Standard Colour White, Black & Green are Made To Order



BRITISH WATER

[www.marshindustries.co.uk](http://www.marshindustries.co.uk) [sales@marshindustries.co.uk](mailto:sales@marshindustries.co.uk)  
T.0044 1933 653570 F.0044 1933 651604